

Gas Hob user manual

Model: H603BG

Thank you for choosing our gas hob.

To use this hob correctly and prevent any potential risk, read these instructions before using the hob.

Keep these instructions in a place where you can find them easily.

If you are unsure of any of the information contained in these instructions, please contact our customer care centre.

The manufacturer shall not be responsible for any damages to persons or property caused by incorrect installation or use of the hob.

The hob has been certified for use in countries other than those marked on the hob.

The manufacturer also reserves the right to make any modifications to the products as may be considered necessary or useful, also in the interests of the user, without jeopardising the main functional and safety features of the products themselves.

The hob is designed for a domestic environment and not a commercial one.

contents

Preface

Safety Warning

- 3 Safety Instructions
- 4 Installation
- 5 Child and People Safety
- 6 During Use
- 8 Cleaning and Service
- 8 Environmental Information

Instructions for use and maintenance


- 9 Description of the appliance
- 10 How to Use the hob
- 12 Safety and Energy saving advice
- 13 Cleaning and Maintenance

Technical instructions

- 15 Using instructions
- 16 Positioning
- 17 Installing the hob
- 18 Gas Connection
- 21 Gas Specifition
- 22 Electrical Connection
- 23 Gas adjustment
- 24 Trouble shooting

Safety Instructions

- Please take the time to read this Instruction Manual before installing or using the hob.
- This instruction booklet must be kept with the appliance for any future reference. If the hob is sold or transferred to another person, ensure the booklet is passed on to the new user.
- The manufacturer declines any liability should these safety measures not be observed.
- The following marks are made to be easily understood so that you can prevent any accident caused by misuse in advance, and use the hob more conveniently.
- Read the following contents thoroughly and ensure you understand them.



The following marks are used in the Instruction Manual as follows:





If gas seems to leak, take the actions as follow:

- Do not turn on the light.

Danger

- Do not switch on/off any electrical hob and do not touch any electric plug.
- Do not use a telephone.
 - 1 Stop using the product and close the middle valve.
 - 2 Open the window to ventilate.
 - 3 Contact our service centre by using a phone outside.



* Gas used contains mercaptan, so that you can smell a gas leak (smell of rotten garlic or egg) even where only 1/1000 of the gas is in the air.

Installation

A Warning

This hob shall be installed in accordance with regulations in force and only used in a well ventilated space.




Where this hob is installed in marine craft or in caravans, it should not be used as a space heater.





Prior to installation, ensure that the gas and electrical supply complies with the type stated on the rating plate.



The gas pipe and electrical cable must be installed in such a way that they do not touch any parts or the hob.



- This appliance should be installed by a qualified technician or installer.
- The adjustment conditions for this appliance are stated on the label or data plate.
- Remove all packaging before using the appliance.
- After unpacking the appliance, make sure the product is not damaged and that the connection cord is in perfect condition. Otherwise, contact the dealer before installing the hob.
- The adjacent cabinetry and all materials used in the installation must be able to withstand a minimum temperature of 85°C above the ambient temperature of the room it is located in, whilst in use.
- In the event of burner flames being accidentally extinguished, turn off the burner control and do not attempt to re-ignite the burner for at least one minute.
- The use of a gas cooking appliance results in the production of heat and moisture in the room in which it is installed. Ensure that the kitchen is well ventilated: keep natural ventilation holes open or install a mechanical ventilation device (mechanical extractor hood).
- Prolonged intensive use of the appliance may call for additional ventilation, for example opening of a window, or more effective ventilation, for example increasing the level of mechanical ventilation where present.

Child and People Safety


A Warning

 Do not allow children to play near or with the hob. The hob gets hot when it is in use. Children should be kept away until it has cooled.


A Caution

- This appliance is designed to be operated by adults.
- Children can also injure themselves by pulling pans or pots off the appliance.
- This appliance is not intended for use by children or other persons whose physical, sensory or mental capabilities or lack of experience and knowledge prevents them from using the hob safely without supervision or instruction by a responsible person to ensure that they can use the hob safely.

During Use



During Use



A Caution

- This hob is intended for domestic cooking only. It is not designed for commercial or industrial purposes.
- Prolonged intensive use of the hob may call for additional ventilation, for example opening of a window, or increasing the level of mechanical ventilation where present.
- Use heat-resistant pot holders or gloves when handling hot pots and pans.
- Do not let pot holders come near open flames when lifting cookware.
- Take care not to let pot holders or gloves get damp or wet, as this causes heat to transfer through the material quicker with the risk of burning yourself.
- Only ever use the burners after placing pots and pans on them. Do not heat up any empty pots or pans.
- Never use plastic or aluminium foil dishes on the appliance.
- When using other electrical appliances, ensure the cable does not come into contact with the hob surfaces of the hob.
- If you have any mechanical parts eg. pacemaker in your body, consult a doctor before using the hob.
- When using glass cookware, make sure it is designed for use on a gas hob. If the surface is made of glass-cracked, switch off the hob to avoid possible electrocution.
- To minimise the possibility of burns, ignition of flammable materials and spillage, turn cookware handles toward the side or center of the cook top without extending over adjacent burners.
- Always turn burner controls off before removing cookware.
- Carefully watch foods being fried at a high flame setting.
- Always heat fat slowly and watch as it heats.
- Foods for frying should be as dry as possible. Frost on frozen foods or moisture on fresh foods can cause hot fat to bubble up and over the sides of the pan.
- Never try to move a pan of hot fat, especially a deep fat fryer. Wait until the fat is completely cool.

Cleaning and Service



Never use abrasive or caustic cleaning agents.



This appliance should only be repaired or serviced by an authorised Service Engineer and only genuine approved spare parts should be used.




\triangle Caution

- Before attempting to clean the appliance, it should be disconnected from the mains and cooled.
- You should not use a steam jet or any other high pressure cleaning equipment to clean the hob.

Environmental Information

- After installation, please dispose of the packaging with due regard to safety and the environment.
- When disposing of an old appliance, make it unusable, by cutting off the cable.




Correct Disposal of This Product (Waste Electrical & Electronic Equipment)

- This marking shown on the product or its literature, indicates that it should not be disposed with other household wastes at the end of its working life. To prevent possible harm to the environment or human health from uncontrolled waste disposal, please separate this from other types of wastes and recycle it responsibly to promote the sustainable reuse of material resources.
- Household users should contact either the retailer where they purchased this product, or their local council, for details of where and how they can take this item for environmentally safe recycling.
- Business users should contact their supplier and check the terms and conditions of the purchase contract. This product should not be mixed with other commercial wastes for disposal.

Top Plate	Dimension Ignition (W*D*H) device		Gas Connection	Electric supply	Burner Feature	ΣQn
Glass	600*510*110	Continuous Ignition Type	G1/2 thread	220-240Vac, 50Hz-60Hz, 0.6W	Wok (1), Semi-rapid (2), Auxiliary (1)	29.56MJ/h

Description of the hob

Accessories



Bracket (4)





Voltage regulator valve (1)



Injector (4)

6

Sponge (4)

Pressure joint(1)





Elbow(1)

Auxiliary pan support (1)




Screw(4)


Instruction Manual (1)

How to Use the hob

The following symbols will appear on the control panel, next to each control knob :




Small flame: minimum setting



- The minimum setting is at the end of the anti-clockwise rotation of the control knob.
- All operation positions must be selected between the maximum and minimum position.
- The symbol on the control panel,next to the control knob will indicate which burner it operates.

Automatic ignition with flame failure safety device

The hob is fitted with a flame failure safety device on each burner, which is designed to stop the flow of gas to the burner head in the event of the flame going out.



To ignite a burner:

- o Press in the control knob of the burner that you wish to light and turn it anti-clockwise to the maximum position.
- o If you keep the control knob depressed, the automatic ignition for the burner will operate.
- O You should hold down the control knob for 15 seconds after the flame on the burner has lit. If after 15s the burner has not lit, stop operating the device and open the closest window or door and/or wait at least 1 min before attempting a further ignition of the burner.
- After this 15-second interval, to regulate the flame you should continue turning the control knob anti-clockwise until the flame is at a suitable level. The operating position MUST be at a position between the maximum and minimum position.
- o To switch the burner off, turn the control knob fully clockwise to the gas off position.
- o In case of power failure, the burners can be lit by carefully using a match.

Safety and Energy saving advice

- The diameter of the bottom of the pan should correspond to that of the burner.

BURNERS	PANS				
DURNERS	min.	max.			
Triple-Crown	200mm	240mm			
Rapid	200mm	240mm			
Semi-Rapid	160mm	180mm			
Auxiliary	120mm	160mm			



Do not use cookware that overlaps the edge of the burner.

	NO	YES				
	Do not use small diameter cookware on large burners. The flame should never come up the sides of the cookware.	Always use cookware that is suitable for each burner, to avoid wasting gas and discolouring the cookware.				
	Avoid cooking without a lid or with the lid half off -as this wastes energy	Place a lid on the cookware.				
	Do not use a pan with a convex or concave bottom.	Only use pots,saucepans and frying pans with a thick,flat bottom.				
	Do not place cookware on one side of a burner,as it could tip over.					
X	Do not use cookware with a large diameter on the burners near the controls, which when placed on the middle of the burner may touch the controls or be so close to them that they increase the temperature in this area and may cause damage.	Always place the cookware right over the burners,not to one side.				
X	Never place cookware directly on top of the burner.	Place the cookware on top of				
	Do not place anything,eg.flame tamer,asbestos mat,between pan and pan support as serious damage to the hob may result.	the trivet.				
X	Do not use excessive weight and do not hit the hob with heavy objects.	Handle cookware carefully when they are on the burner.				




- It is not recommended to use roasting pans, frying pans or grill stones heated simultaneously on several burners because the resulting heat build-up may damage the hob.
- Do not touch the top plate and trivet whilst in use for a certain period after use.



As soon as a liquid starts boiling,turn down the flame so that it will barely keep the liquid simmering.



- Cleaning operations must only be carried out when the appliance is completely cool.
- The appliance should be disconnected from your mains supply before commencing any cleaning process.
- Clean the appliance regularly, preferably after each use.
- Abrasive cleaners or sharp objects will damage the appliance surface; you should clean it using water and a little washing up liquid.



Pan support, Control handles

- Take off the Pan support.
- Clean these and the control handles with a damp cloth, washing up liquid and warm water. For stubbon soiling, soak beforehand.
- Dry everything with a clean soft cloth.

Top plate


- Regularly wipe over the top plate using a soft cloth well wrung-out in warm water to which a little washing up liquid has been added.
- Dry the top plate thoroughly after cleaning.
- Thoroughly remove salty foods or liquids from the hob as soon as possible to avoid the risk of corrosion.
- Stainless steel parts of the appliance may become discoloured over time. This is normal because of the high temperatures. Each time the hob is used these parts should be cleaned with a product that is suitable for stainless steel.

Cleaning and Maintenance

BURNERS

- Remove the burner lids and Flame Spreaders by pulling them upwards and away from the top plate.
- Soak them in hot water and a little detergent or washing up liqui.
- After cleaning and washing them, wipe and dry them carefully. Make sure that the flame holes are clean and completely dry.
- Wipe the fixed parts of the burner cup with a damp cloth and dry afterwards.
- Gently wipe the ignition device and flame supervision device with a well wrung-out cloth and wipe dry with a clean cloth.
- Before placing the burners back on the top plate, make sure that the injector is not blocked.

Re-assemble the Auxiliary, Semi-Rapid, Rapid and Triple-Crown burners as follows :



- 1.Place the flame spreader (4) on to the burner cup (5) so that the ignition device and the flame supervision device extend through their respective holes in the flame spreader.The flame spreader must click into place correctly.
- 2.Position the burner lid (1,2,3) onto the flame speader (4) so that the retaining pins fit into their respective recesses.




Replace parts in the correct order after cleaning.

- Do not mix up the top and bottom.
- The locating pins must fit exactly into the notches.

Using instructions


- Do not modify this appliance.
- This appliance must be installed by an authorised technician or installer.
- Prior to installation, ensure that the local distribution conditions (nature of the gas and gas pressure) and the adjustment of the appliance are compatible.
- The adjustment conditions for this appliance are stated on the label (or data plate).
- This appliance is not connected to a combustion products evacuation device. It should be installed and connected in accordance with current installation regulations. Particular attention should be given to the relevant requirements regarding ventilaton.
- Before installing, turn off the gas and electricity supply to the appliance.
- All appliances containing any electrical components must be earthed.
- Ensure that the gas pipe and electrical cable are installed in such a way that they do not touch any parts of the hob which may become hot.
- Gas pipe or connector shouldn't be bent or blocked by any other appliances.
- Check the dimensions of the appliance as well as the dimensions of the gap to be cut in the kitchen unit.
- The panels located above the work surface, directly next to the appliance, must be made of non-flammable material. Both the materials and the glue used to secure it should be heat resistant, to prevent deterioration.
- Turn on appliance tap and light each burners. Check for a clear blue flame without yellow tipping. If burners shows any abnormalities check the following :
 - Burner lid on correctly
 - Flame spreader positioned correctly
 - Burner vertically aligned with injector nipple
- A full operational test and a test for possible leakages must be carried out by the fitter after installation.
- The flexible hose shall be fitted in such a way that it cannot come into contact with moveable part and does not pass through any space susceptible of becoming congested.

Positioning




This hob is to be built into a kitchen unit or 600mm worktop, providing the following minium distances are allowed;


- o The edges of the hob must be a minimum distance of 60 mm from a side or rear wall.
- o 750 mm between the highest point of the hob surface (including the burners) and the underside of any horizontal surface directly above it.
- o 400 mm between the hob surfaces, providing that the underside of the horizontal surface is in line with the outer edge of the hob. If the underside of the horizontal surface is lower than 400 mm, then it must be at least 50 mm away from the outer edges of the hob.
- o 50 mm clearance around the hob and between the hob surface and any combustible materials.
- You must have a gap of at least 25 mm and at most 74 mm between the underneath of the hob and any surface that is below it.




- An oven must have forced ventilation to install a hob above it.
- Check the dimensions of the oven in the installation manual.
- The cut out size must be that which is indicated.


Installing the hob





Bottom view





1. Remove the pan supports, the burner lid and flame spreader and carefully turn the hob upside down and place it on a cushioned mat.

Take care that the Ignition devices and flame failure devices are not damaged in this operation.

- 2. Apply the sponge provided around the edge of the hob.
- 3. Do not leave a gap in the sealing agent or overlap the thickness.

Sponge

The thickness of the sponge is 3 mm. The width of the sponge is 10 mm.



Do not use a silicon sealant to seal the hob against the cutout surface.

This will make it difficult to remove the appliance in future, particularly if it needs to be serviced.

1. Place the bracket (B) over the holes that match the size of the screws.There are one set of screw holes in each corner of the hob (H).

Slightly tighten a screw (C) through the bracket (B) so that the bracket is attached to the hob, but so that you can still adjust the position.

- 2. Carefully turn the hob back over and then gently lower it into the aperture hole that you have cut out.
- On the underneath of the hob, adjust the brackets into a position that is suitable for your worktop.
 Then fully tighten the screws (C) to secure the hob into position.

Gas Connection



This appliance must be installed and connected in accordance with installation regulations in force in the country in which the appliance is to be used.



Turn off power for safety and hob protection. Close middle valve to prevent gas leakage.



Keep away from inflammable materials around hob. Before work, put on gloves.

CAUTION Cool off the hob for a while right after using hob for your safety because you can get burners by high temperature from the hob.

Most of the tools that you might need are shown below. Some are optional.

ltem	How to use	Pictures
Screw driver	Use for assembly and disassembly of all screws	
Tubing Wrench	Use for assembly and disassembly of tubing to the burner cup	20
7mm Vox Driver	Use for assembly and disassembly of injector nozzles.	-

Replacement of gas-type fitting

Tool: Open-end wrench

Steps for operation:

A: Disassemble with a wrench the gas-type fittings from main gas tube.

When you disassemble/assemble gas connection, use 2 spanners. One for fixing gas connection elbow, the other for tightening gas hose.



B: Lock tightly a replaceable gas-type fitting onto the main gas tube.

Gas Connection


Statutory requirements


This installation must conform with the following:

- Manufacturer's Installation instructions
- Local Gas Fitting Regulations
- NZ Building Codes
- Refer to AS/NZS 5601.1 for Gas Installations
- S.A.A. Wiring Code
- Local Electrical Regulations
- Any other statutory regulations

Preparing to install

Refer to AS/NZS 5601.1 for piping size details. These built-in hobs are intended to be inserted in a benchtop cutout. Only an officially authorised technician should connect the hob. Before you begin, turn off the gas and electricity supply.





- Access to the whole length of the connection hose must be possible and the gas hose must be replaced before its use before the end of service life (indicated on the hose.)
- Before Leaving-Check all connections for gas leaks with soap and water.
- DO NOT use a naked flame for detecting leaks. Ignite all burners both individually and concurrently to ensure correct operation of gas valves, burners and ignition. Turn gas taps to low flame position and observe stability of the flame for each burner individually and all together. Adhere the duplicate data plate to an accessible location near the hob. When satisfied with the hobs operation, please instruct the user on the correct method of operation. In case the hob fails to operate correctly after all checks have been carried out, refer to the authorised service provider in your area.

Gas Connection

- Flexible Hose: If installing with a hose assembly, it must comply with AS/NZS 1869,10mmID,class B or D,no more than 1mm long and installed in accordance with AS/NZS 5601.1.
- Ensure that the hose does not contact the hot surfaces of the hob,oven,dishwasher or any other appliance that may be installed underneath or next to the hob. The hose should not be subjected to abrasion, kinking or permanent deformation and should be able to be inspected along its entire length with the hob in the installed position. Unions compatible with the hose fittings must be used and all connections tested for gas leaks. The supply connection point shall be accessible with the hob installed.
- WARNING: Ensure that the hose assembly is restrained from accidental contact with the flue outlet of an underbench oven.

Gas Connection

Install in accordance with relevant gas standards and/or codes of practice applicable.

Connect the elbow fitting to the hobs gas manifold connection, and check that seals between the elbow and manifold connection are in place and in good condition.

- For Natural gas: connect the natural gas hob regulator (pictured opposite) with integral test point using approved gas thread tape or compound to the elbow fitting.
- For Universal LPG: connect the brass test point adaptor (pictured opposite) using approved gas thread tape or compound to the elbow fitting.

Ensure the supply connection point, test point and natural gas regulator adjustment screw (for Natural gas installation) are accessible for testing and/or adjustment with the hob in the installed position.







Where a flexible hose assembly is used, ensure it is approved to AS/NZS 1869, Class B. Any hose assembly used must be restrained from accidental contact with the flue outlet of an under bench oven.

This hose assembly shall be suitable for connection to a fixed consumer piping outlet located as follows:

Hob at a point 800 mm to 850 mm above the floor and in the region outside the width of the hob to a distance of 250 mm.

After connecting to gas, check for leaks using soapy solution, never a naked flame.






Gas type &	Heat input and orifice size marked(mm)					
pressure	Wok burner	Rapid burner	Semi-rapid	Auxiliary-rapid		
	12.96MJ/h	/	6.3MJ/h	4.0MJ/h		
Propand 2.75kPa	0.97	/	0.68	0.56		
Natural Gas 1.0kPa	1.60	/	1.12	0.90		

- This appliance must be earthed.
- This hob is designed to be connected to a 220-240V, 50Hz-60Hz AC electricity supply.
- The wires in the mains lead are coloured in accordance with the following code;
 - Green/yellow = Earth
 - Blue = Neutral
 - Brown = Live

The wire which is coloured green and yellow must be connected to the terminal which is marked with the letter E or by the earth symbol.

WIRING DIAGRAM



When the power cord is damaged it must be replaced by the manufacturer , service agent or similarly qualified personnel.

Gas adjustment


- Take precautions on the operations and adjustments to be carried out when converting from one gas to another.
- All work must be carried out by a qualified technician.
- Before you begin, turn off the gas and electricity supply to the appliance.

Change the injector of the burners.

Remove the pan support, Burner lid and Flame spreader.

Unscrew the injector using a 7mm box spanner and replace it with the stipulated injector for new gas supply. Carefully reassemble all components. After injectors are replaced, it is advisable to firmly tighten the injector in place.

Adjustment of minimum level of the flame.



- ① Turn the taps down to minimum.
- ⁽²⁾ Remove the knob from the tap and place a small bladed screwdriver in the centre of the tap shaft.
- ^③ The correct adjustment is obtained when the flame has a length of about 3 4 mm.
 - For butane/ propane gas, the adjusting screw must
 be tightly screwed in.
 - Refit the control knob.

Make sure that the flame does not go out by quickly turning from maximum flow to minimum flow. If it does then remove the control knob and make further adjustments to the gas flow, testing it again once the adjustment has been made.

^④ Repeat this process for each one of the gas taps.



Do not dismantle the tap shafe: in the event of a malfunction, change the whole tap.

- Before placing the burners back in place, make sure that the injector is not blocked.
- A full operational test and a test for possible leakages must be carried out after gas conversion. (such as soap water or gas detector)
- After completing conversion, a qualified technician or installer has to mark "V" on the right gas category to match with the setting in rating plate. Remove the previous setting "V" mark.

Trouble shooting

- Repairs should be performed by a licensed technician only.Improper repair may result in considerable danger to you and others.
- However, some minor problems can be resolved as follows :

Problem	Probable cause	Solution		
	No Spark.	Check the electricity supply.		
Not ignited	The burner lid is badly assembled.	Assemble the lid correctly.		
	The gas supply is closed.	Open the gas supply completely.		
Badly ignited	The gas supply is not completely open.	Open the gas supply completely.		
	The burner lid is badly assembled.	Assemble the lid correctly.		
	The ignition plug is contaminated with alien substance.	Wipe alien substance with a dry cloth.		
	The burners are wet.	Dry the burners lids carefully.		
	The holes in the flame spreader are clogged.	Clean the flame spreader.		
Noise made when combusted and ignited	The burner lid is badly assembled.	Assemble the burner lid correctly.		
Flame goes out when in use.	The flame failure device is contaminated with alien substance.	Clean the flame failure device.		
	Product being cooked has boiled over and extinguished the flame.	Turn off burner knob.Wait one minute and reignite zone.		
	A strong draught may have blown the flame out.	Turn off zone and check cooking area for draught such as open windows.Wait one minute and reignite zone		
Yellow Flame	The holes in the flame spreader are clogged.	Clean the flame spreader.		
	Different gas is used.	Check the gas used.		
Unstable Flame	The burner lid is badly assembled.	Assemble the burner lid correctly.		
Gas Smell	Gas leakage	Stop using the hob and close the middle valve.Open the window to ventilate. Contact our service centre by using a phone outside.		



■ If problem is not solved, please contact an authorised service centre.

AWARD APPLIANCES (NZ) LTD WARRANTY STATEMENT

Please	con	nplete	the foll	lowing details	when y	vou unp	ack the	product	: and	d retain t	his card	with th	e purch	nase
invoice	or	sales	docket.	. Verification	of the	date c	f purcha	ase will	be	required	should	service	under	the
warrar	ty b	e sou	ght.											

Model Number	
Date of Purchase	
Retailers / Dealers Name	

WARRANTY

This product is covered by a Warranty in addition to all rights available to you by statute. The Warranty is for a period of **twenty-four (24) months** from the date of purchase, subject to the conditions below. Registering your appliance online at <u>www.awardappliances.co.nz</u> will qualify your purchase for an **additional twelve (12) months warranty cover on parts only**.

The Warranty covers rectifications of faults arising from defective materials, components, faulty workmanship or assembly. The product will be repaired or replaced at the sole discretion of Award Appliances (NZ) Ltd.

Conditions of Warranty:

- 1. The purchaser/installer carefully follows the installation instructions provided and complies with electrical, gas, plumbing, building and other regulations and codes of practice in New Zealand;
- 2. That the purchaser carefully follows the instructions provided in the owner's handbook relating to the proper use and care of the product;
- The product is not used for any purpose other than the domestic use for which it has been designed. Use for commercial purposes or any application outside of a residential dwelling, shall reduce the warranty period to three (3) months from date of purchase.
- 4. That the product was purchased and installed in the North or South Islands of New Zealand

This Warranty does not extend to:

- (a) Lamps/LED, filters, blockages/restrictions, incorrect detergents, incorrect or poor installations, incorrect use.
- (b) Back feeding from waste disposal units, vermin/insect damage or transit protection left installed.
- (c) Damage to surface coatings caused by cleaning or maintenance using products not recommended by the manufacturer; tin foil on oven base, leaving a baking sheet or tray on oven base.
- (d) Defects caused by normal wear and tear, accident, negligence, alteration or misuse.
- (e) Damage caused by spill-overs, lack of maintenance, or impact.
- (f) Damage or faults caused by incorrect power supply, power surges or storm damage.
- (g) Any damage or fault arising from installation of the product.
- (h) A product dismantled, repaired or serviced by any person other than an authorised employee or service agent as appointed by Award Appliances (NZ) Ltd.
- (i) Any additional travelling costs beyond 30km from an appointed service agent.

If you are unable to establish the date of purchase, or the fault is not covered by this Warranty, or if the product is found to be in working order, you will be required to bear all service charges. Please present this notice to the service person, together with proof of purchase. The warranty is non-transferable.

For service please telephone (03) 348 0556

AWARD APPLIANCES (NZ) Ltd

382 Blenheim Road CHRISTCHURCH Telephone: (03) 348 0556 Email: service@award.co.nz www.awardappliances.co.nz

version number: V20200224